



XTG 80W90 TDL

DESCRIPTION

Universal extreme pressure synthetic oil formulated for the lubrication of mechanical transmissions and heavy-duty gears, bridges, differentials, gearboxes submitted to difficult operating conditions (heavy loads, high speed and temperature), final reductions and transfer boxes.

APPLICATION

Bardahl XTG 80w90 TDL is particularly suitable for highly charged hypoid gears. For manual boxes and differentials. Total Drive Line.

SPECIFICATIONS

This product offers the following performance level:

API	GL-3/ GL4/ GL5/ MT1
ZF	TE-ML 02B/04G/05A/07A/12L/12M/ 16B/16C/16D/17H/21A
MIL	MIL-L-2105D/MIL-PRF-2105E
SAE	J2360
DAF	DAF
MAN	341 Typ Z2 / 342 Typ M2
Scania	STO 1:0
MB	235.0
MACK	GO-J
Iveco	Iveco

PROPERTIES

- ✓ Offers a very good resistance to high temperature,
- ✓ Offers very strong extreme pressure (EP) properties,
- ✓ Has a low pour point,
- ✓ Provides a high resistance against corrosion and oxidation,
- ✓ Provides anti-wear and antifoam properties.





TECHNICAL DATA

Density at 15°C	Kg/l	0,887
Viscosity at 40°C	mm ² /s	125,8
Viscosity at 100°C	mm ² /s	15,00
Viscosity index		122
Flash point COC, °C	°C	234
Pour point, °C	°C	-36

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

RECOMMENDATIONS

Handling : any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 60 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

34981	12 x 1 L
34983	3 x 5 L
34988	20 L
34984	60 L
34987	205 L

