

# **XTEC OW30 F**

# DESCRIPTION

New generation fully synthetic engine oil developed to avoid fuel overconsumption and extend the lifespan of the DPF. Formulated from last generation performance additives.

## **APPLICATION**

**Bardahl XTEC 0w30 F** improves the consumption of the fuel, fuel economy and reduces the formation of post-combustion residues. The XTEC 0w30 F can be used in any diesel or petrol engine with turbo-charged or not (VL or VU) with the following performance level Ford Ford WSS-M2C950-A. This oil can be used on vehicles equipped with 3 way-catalytic converters.

## **SPECIFICATIONS**

This product offers the following performance level:

FORD	WSS-M2C950-A
ACEA	C2
JAGUAR LAND ROVER	STLJR.03.5007

## PROPERTIES

- $\checkmark$  Lower fuel consumption,
- ✓ Offers excellent dispersion and detergency properties,
- ✓ Makes cold starting easier even at very low temperature,
- ✓ Strong resistance against oxidation,
- ✓ Anti-foam,
- ✓ Anti-wear,
- ✓ Anti-corrosion,
- ✓ High and stable viscosity index,
- ✓ Low SAPS,
- $\checkmark~$  Safe lubrication film at high temperatures.





# **TECHNICAL DATA**

Density at 15°C	Kg/l	0,845	
Viscosity at -35°C	mPa.s	5800	
Viscosity at 40°C	mm2/s	49,30	
Viscosity at 100°C	mm2/s	10,00	
Viscosity index		189	
Flash point COC, °C	°C	230	
Pour point, °C	°C	-45	
TBN alcalinity	mgKOH/g	7,7	
Sulphated ash contents	%	0,80	

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

#### RECOMMENDATIONS

<u>Handling</u>: any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

<u>Storage</u> : it is recommended to use the product within 60 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

#### **REFERENCES & AVAILABILITIES**

36851	12 x 1L
36853	3 x 5L
36858	20L
36854	60L
36857	205L



SADAPS BARDAHL ADDITIVES & LUBRICANTS Rue du Mont des Carliers, 3 ZI TOURNAI Ouest, 2 T: (+32) (0) 69 59 03 60