

ATF 8 Gear

DESCRIPTION: High quality synthetic automatic transmission fluid with low viscosity for a more responsive transmission. Suitable for automatic transmissions.

APPLICATION: Bardahl ATF 8 Gear has excellent stability and fluidity at low temperatures. Ideal for cold starts. The **ATF 8 GEAR** can be used in many automatic transmissions and has been formulated for the lubrication of ZF 8HP (8HP45, 8HP55, 8HP70, 8HP90 ...) transmissions as it has a strong fuel economy contribution. It can also be used for some 6HP (VAG, BMW models).

SPECIFICATIONS

This product meets the following performance levels:

VAG	G 052 533 / G 055 005 / G 055 540 / G 055 162 / G 060 162
BMW	83 22 0 142 516 / 83 22 2 152 426 / 83 22 0 397 114 / 163 514
MB	236.41
JAGUAR	FLUID 8432
MITSUBISHI	ATF - J3
MAZDA	FZ
MERCON	LV
GM	DEXRON VI/AW1 88863400 / 88863401
JASO	M315 Class 1A
TOYOTA	TYPE WS
AISIN WARNER	JWS 3324
NISSAN	MATIC S
SHELL	M-1375.4 / ATF 3353/154
FORD	XT-6-QSP
HONDA	ATF-DW1
HYUNDAI	SP-IV / SPH-IV / NWS-9638 T-5 / 040000C90SG
PORSCHE	000 043 304 000
FIAT	9.55550-AV5
ZF	LIFEGUARDFLUID 6-8
BENTLEY	PY112995PA



LAND ROVER	TYK500050 / LR0022460
MASERATI	231603

PROPERTIES

- ✓ **High viscosity index** ensuring good stability,
- ✓ Longer lifespan,
- ✓ **Very low pour point**,
- ✓ Very good thermal stability and anti-oxidation protection,
- ✓ Anti-wear, anti-corrosion and anti-foam,
- ✓ High-performance anti-friction additives,
- ✓ Inert for seals and non-ferrous metals,
- ✓ Good resistance to vibrations,
- ✓ Quick commissioning during cold starts,
- ✓ Viscosity to avoid overconsumption (fuel economy),
- ✓ **Dark yellow color.**

TECHNICAL DATA

Density at 15°C	Kg/l	0,843
Viscosity 40°C	mm ² /s	30
Viscosity 100°C	mm ² /s	6,1
Viscosity Index		155
Flash point COC, °C	°C	>200
Pour point, °C	°C	-42
Alkalinity TBN	mgKOH/g	n/A

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

RECOMMENDATIONS

Handling: All safety information on the handling and use of this product is provided in the Material Safety Data Sheet. Always check the manufacturer car manual before use.

Storage: it is recommended to use the product within 60 months. It must be stored in the original sealed packaging, protected from light, moisture and excessive temperatures.

REFERENCES & PACKING

36871	12 x 1L
36873	3 x 5L
36878	20L
36874	60L
36877	205L